



TATSA[®]
CALIDAD INDUSTRIAL DESDE 1955



L.P. GAS DISPENSER STATION TANK



GENERAL SPECIFICATIONS

Designed and manufactured in accordance with Mexican Specifications.

SPECIFICATIONS

Design pressure 250 PSI.
Hydrostatic test pressure 1.3 times the design pressure.
Design temperature 125°F.
Longitudinal welding seam full X-ray.
Girth seams spot X-ray.

FINISH

Inside cleaned.
White Polyurethane paint.

* NOT APPLICABLE FOR VERTICAL TANKS

TECHINCAL DATA

MODEL	NOMINAL CAPACITY		WEIGHT		FILL WATER WEIGHT		DIAMETER		LENGHT		TOTAL HEIGHT		MODELS	
	LITERS	U.S. GALLONS	KG	POUNDS	KG	POUNDS	METERS	INCHES	METERS	INCHES	METERS	INCHES	A	B
2,200 H	2,200	581	468	1,029	2,668	5,882	1.04	40.96	3.00	118.13	2.21	87.38	X	
2,200 H	2,200	581	592	1,305	2,792	6,155	1.04	40.96	3.00	118.13	2.21	87.38		X
3,400 H	3,210	848	700	1,545	3,910	8,620	1.04	40.96	4.20	165.66	2.21	87.38	X	
3,400 H	3,210	848	824	1,817	4,034	8,893	1.04	40.96	4.20	165.66	2.21	87.38		X
5,000 H	4,913	1,298	1,081	2,383	5,994	13,215	1.18	46.77	4.73	186.56	2.36	93.25	X	
5,000 H	4,913	1,298	1,025	2,657	6,118	13,488	1.18	46.77	4.73	186.56	2.36	93.25		X
5,000 V	4,913	1,298	1,532	3,377	6,445	14,209	1.18	46.77	1.37	54.06	5.88	231.31	X	
5,000 V	4,913	1,298	1,656	3,650	6,569	14,482	1.18	46.77	1.37	54.06	5.88	231.31		X

H= HORIZONTAL V= VERTICAL

A= BÁSIC B= WITH FITTINGS

VALVES AND FITTINGS	2200 H		3400 H		5000 H		5000 V	
	TYPEA	TYPEB	TYPEA	TYPEB	TYPEA	TYPEB	TYPEA	TYPEB
(1) Float gauge (magnetic)	X	X	X	X	X	X		
(3) Float gauge (magnetic)							X	X
Service valve CGA 510 (F. Pol connection) [3/4" M. NPT container connection]	X	X	X	X	X	X		
Válvula de nivel de líquido	X	X	X	X	X	X	X	X
Fill valve 1 3/4" M. Acme (1 1/4" NPT Container connection)	X	X	X	X	X	X	X	X
Relief valve (1" NPT container connection)	X	X						
Relief valve 1 1/4" NPT Cointainer connection			X	X	X	X	X	X
Vapor valve (1 1/4" M. Acme 3/4" NPT container connection)	X	X	X	X	X	X	X	X
Drain coupling 3/4"	X	X	X	X	X	X		
Drain coupling 1 1/4"							X	X
Discharge coupling 1 1/4"	X	X	X	X	X	X		
Discharge coupling 2"							X	X
Excess flow valve 1 1/4" F. NPT (1 1/4" NPT container connection)		X		X		X		X
Excess flow valve "check lock" 3/4" F NP (3/4" NPT container connection)							X	X
By-Pass coupling 3/4"	X	X	X	X	X	X	X	X
Back pressure valve 3/4" F. NP (3/4" NPT container connection)		X		X		X		X
Vapor equalizing coupling 3/4"					X	X		
Thermometer					X	X	X	X
Pressure gauge					X	X	X	X
Zarco colander 1 1/4"		X		X		X		X
By-Pass valve 3/4"		X		X		X		X
Electric power pump 3/4 HP		X		X		X		X
Globe valves 1 1/4" & 3/4"		X		X		X		X
Quick-acting hose-end valve 1"		X		X		X		X
8 meters of 1" diameter hose		X		X		X		X
Valve guard	X	X	X	X	X	X		
Saddles	X	X	X	X	X	X		
Legs							X	X
Ladder	X	X	X	X	X	X	X	X
Lifting lugs	X	X	X	X	X	X	X	X
Hose holder		X		X		X		
External pipe							X	X
Dispenser							*	*

*SPECIAL REQUEST ONLY